

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094

PO Box 189 - Westwego, LA 70096



PRODUCT BULLETIN

FUEL POWER plus LUBRICITY

Diesel Fuel Additive

General Description

FUEL POWER plus LUBRICITY is formulated to improve fuel efficiency of diesel powered engines (direct or indirect injected) that will, based upon the operators preference, either reduce fuel consumption or increase power output from their existing engine fleet. **FUEL POWER plus LUBRICITY** is formulated with a proprietary lubricant technology will reduce wear and thus extends engine component life resulting in an overall reduction in maintenance expenses. **FUEL POWER plus LUBRICITY** will provide a more reliable and smoother running engine fleet. **FUEL POWER plus LUBRICITY** reduces exhaust emissions, allowing owners and operators of these engines operators to positively impact the environment and address tightening emissions regulations. **FUEL POWER plus LUBRICITY** provides its multifunctional benefits without harmful side effects and without contribution to any emissions or combustion products considered harmful to the environment.

Using **FUEL POWER plus LUBRICITY** will lower fuel requirements, reduce exhaust gas temperatures, reduce carbon deposits, lower coefficient of friction, and reduce emissions. The operator can expect 5 - 10% minimum improvement in fuel efficiency. Low speed (stop and go, school buses, waste disposal trucks) engines have seen mpg go up after one tankful.

Use

FUEL POWER plus LUBRICITY should be added to the tank before filling to assure adequate mixing prior to use. One gallon of **FUEL POWER plus LUBRICITY** will treat 1000 gallons of diesel fuel (one ounce per 8 gallons of diesel fuel).

Physical Properties

Color	Amber Liquid
Odor	Mild Solvent
Specific Gravity	7.5 - 8.0
Flash Point	~ 115° F
Solubility	Soluble in Hydrocarbons

Availability

FUEL POWER plus LUBRICITY is available in UN approved One gallon containers, 5 gallon pails, 55 gallon drums and bulk quantities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.

The information contained herein is provided in good faith, but shall not create any warranty, expressed or implied, by operation of law or otherwise, with any respect to any product. JMN SPECIALTIES, INC. SPECIFICALLY DISCLAIMS ALL WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Phone (504) 341-3749 Fax (504) 341-5868 or E-mail: sales@jmnspecialties.com