# JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094 PO Box 189 - Westwego, LA 70096



### PRODUCT BULLETIN

## **BIODIESEL FUEL POWER**

### Fuel Additive

#### General Description

**Biodiesel Fuel Power** is a premium fuel additive specifically formulated to provide significant performance benefits in all diesel fuels, including ultra-low sulfur diesel and bio-diesel fuel blends.

Biodiesel and biofuels contain varying amounts of methyl ester, (either soy or tallow based oil) to improve emissions and to create a renewable energy resource. However, these oils increase the propensity of the fuel to absorb water from the atmosphere. This can act as a nutrient base for bacteria and fungi growth which can cause the fuel to age much faster and possibly form sludge and deposits in the fuel system. **Biodiesel Fuel Power** is formulated to absorb and disperse water in all blends of biodiesel. This allows the fuel to be combusted, slows down the aging of biodiesel and helps to prevent the formation of sludge and deposits. By controlling water in biodiesel, **Biodiesel Fuel Power** will reduce the potential for bacteria and fungi growth.

Regular use of **Biodiesel Fuel Power** will totally disperse water in the fuel system, help clean and keep clean the injector system, fuel tanks, and lines. Stabilized fuel will result in reduction of gums and varnishes, improves combustion, and prevent sludge formation. This formulation is alcohol free.

#### Use

**Biodiesel Fuel Power** should be added to the tank before filling to assure adequate mixing prior to use. One gallon of **Biodiesel Fuel Power** will treat 2000 gallons of diesel fuel (one ounce per 16 gallons of biofuel).

#### **Physical Properties**

ColorAmber LiquidOdorMild SolventSpecific Gravity7.5 - 8.0Flash Point $> 145^{\circ}$  F

Soluble in Hydrocarbons

#### **Availability**

**Biodiesel Fuel Power** is available in UN approved One gallon containers, 5 gallon pails, 55 gallon drums and bulk quantities.

#### Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.