



PRODUCT BULLETIN

ODOR ELIMINATOR 53

Odor Control Solution

General Description

ODOR ELIMINATOR 53 is an environmentally safe, liquid, malodor eliminator and neutralizer used for industrial based odors consisting of sulfides, mercaptans, amines, waste hydrocarbon or vegetable oils, human or animal waste, fish remains, or other strong industrial malodors. **ODOR ELIMINATOR 53** is a natural, environmentally safe product so technologically advanced, that after the odor is eliminated, only a clean air smell remains. **ODOR ELIMINATOR 53** contains a catalyst that helps to remove offensive odors by chemically attaching to the malodor and neutralizing them.

Application

ODOR ELIMINATOR 53 can be batch treated into the liquid malodor source or atomized and/or sprayed into the atmosphere for complete neutralization of emissions. Due to varying concentrations in liquids, titration of solutions with **ODOR ELIMINATOR 53** is recommended to get precise treating ratios. For fogging, starting recommended dilution is 10:1, (5 gallons of liquid per 50 gallons of water). Selection of wet, damp, or dry fog is determined on location based upon odor levels and discharge stream. Adjust up or down as needed to control liquid. Dilutions as low as 2 to 4 ounces per gallon have been found to be effective in controlling most light to medium malodors.

Physical Properties

Odor	Fresh Fruity Odor
Solubility	Dispersible in water
Specific Gravity in H ₂ O	0.994
pH	7.0
Freezing Point	32° F
Boiling Point	212° F
Flash Point	Non-Flammable

Availability

ODOR ELIMINATOR 53 is available in UN approved 5 gallon, 6 gallon pails, 20 gallon, 30 gallon and 55 gallon drum quantities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.