

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094
PO Box 1519 - Gretna, LA 70054-1519



PRODUCT BULLETIN

TEKVIS-L

Liquid Viscosifier

General Description

TEKVIS-L is a liquid viscosifier designed to provide rapid and uniform viscosity development in drilling, completion, workover fluids and fluids used in water well and seismic operations. High concentrations can be used separately or in circulation problems.

Physical Properties

Specific Gravity, 60/60°F	9.25
pH, 2 lbs./bbl. Fresh Water	7.0
Pour Point, ° F	26 (Keep above freezing)
Flash Point, ° F	> 200

Use & Recommendations

1. Will provide rapid and uniform viscosity in wide range of water-based drilling, completion and workover fluids.
2. Will provide rapid viscosity development in water well and seismic drilling operations.
3. Will reduce sloughing, swelling and dispersion of sensitive shales under certain conditions.
4. Will provide excellent characteristics during Nitrogen/coil tubing operations.
5. Will provide fluid loss control when used in conjunction with other drilling mud additives.
6. Can be broken and removed by acidizing, enzymes or oxidizing.

Availability

TEKVIS-L is available in UN approved 5 gallon pails, 55 gallon drums and bulk quantities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.