

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094
PO Box 1519 - Gretna, LA 70054-1519



PRODUCT BULLETIN

ABS-HT

Asbestos Binding Solution - High Temp

General Description

ABS-HT is a non-toxic, multi-purpose, ready-to-use, low pressure airless spray applied wetting and penetrating encapsulant for all forms of friable asbestos. **ABS-HT** can be used for the encapsulation of ACM (Asbestos Containing Material) so that they can remain in use without contributing to air-borne asbestos. **ABS-HT** securely adheres to and *binds* friable ACM. When encapsulating ACM to remain in service, **ABS-HT** need only be applied as a thin film to the exposed (air stream) surfaces. **ABS-HT** can be used as a removal encapsulant when applied as a saturant. **ABS-HT** can then be misted over the work area as a lock down encapsulant to seal any remaining asbestos fibers to the substrate. When dry, **ABS-HT** forms a clear, non-abrasive, flexible film for safe and effective handling of ACM. **ABS-HT** has a temperature stability of 600° F. Coverage is dependent upon density and type of ACM being coated.

Application

ABS-HT must be applied with a low pressure airless sprayer.

Physical Properties

Color	White (or various tinted colors)
Odor	Slight Ammonia
Coverage	400 - 600 sq. ft./gal
Density	1.030
pH	< 10
Flash Point	None
Solubility	Soluble in Water
VOC (Volatile Organic Compounds)	None

Availability

ABS-HT is available in 5 gallon pail, 55 gallon drums and bulk quantities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.