

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094
PO Box 1519 - Gretna, LA 70054-1519



PRODUCT BULLETIN

RP-606

Heavy Duty Cosmoline Protective Coating

General Description

RP-606 is an dark colored, high melting point, resilient coating designed to provide long term protection of metal surfaces. **RP-606** is applied as a solution in a volatile solvent. The residual film, after solvent evaporation, is highly resistant to salt water and salt spray. **RP-606** is supplied pre-dispersed in mineral spirits to simplify handling and application of the product.

Performance Results

Neat RP-606	Film Thickness		Days to Fail Humidity Cabinet on Polished Steel	Days to Fail 5% Salt Spray
	Mils	Microns		
	4.00	101.6	60+	60+

Application

RP-606 can be applied by dipping the parts to be protected in a vat or spraying the parts to be protected with air sprayers, pump type sprayers or by pouring the product over the parts. Removal of protective films is accomplished by using a steam cleaner or washing the parts in mineral spirits.

Physical Properties

Appearance	Thick, Dark Brown Liquid
Odor	Solvent Odor
Specific Gravity	0.90
Flash Point (minimum)	108 ^B F
Melting Point	Liquid as Provided

Various blends of **RP-606** meet or exceed the following MIL-SPECS: MIL-C-83933, MIL-C-0083933A (MR), MIL-C-16173E, Grade 4, Mil-C 11796 class 3, Class I, MIL-C-62218 (AT).

Availability

RP-606 is available in UN approved 5 gallon pail, 55 gallon drums and bulk quantities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.

The information contained herein is provided in good faith, but shall not create any warranty, expressed or implied, by operation of law or otherwise, with any respect to any product. JMN SPECIALTIES, INC. SPECIFICALLY DISCLAIMS ALL WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Phone (504) 341-3749 Fax (504) 341-5868 or E-mail: info@jmnspecialties.com