

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094
PO Box 1519 - Gretna, LA 70054-1519



PRODUCT BULLETIN

QUICK DRY 200

Non-Chlorinated Safety Solvent

General Description

Quick Dry 200 was made especially for generator and electrical motor cleaning and degreasing. **Quick Dry 200** is formulated with pure aliphatic solvents that have a high evaporation rate and will not leave a residual film. **Quick Dry 200** will have no deleterious effect on wiring, metal, or plastic. This product does not contain Methyl Chloroform (111 Solvent) or any other type of Chlorinated Solvent.

Quick Dry 200 may be used on grease, oil, hydrocarbons, paraffins and resins. It is nonflammable, non-corrosive and non-conductive; it is self-evaporating at ambient temperatures and it does not leave a residue.

Application

Apply as a spray or a wipe. Spray undiluted on all parts for best results. **Quick Dry 200** may be diluted with kerosene, diesel or other high flash solvents for economy in general degreasing of equipment.

Physical Properties

Specific Gravity	.80 - .85
Dielectric Strength	35,000 volts
KB Value	36 - 40
Boiling Point	> 160° F
Flash Point	> 140° F

Availability

Quick Dry 200 is available in UN approved 5 gallon pails, 55 gallon drums and bulk quantities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.