# JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094 PO Box 1519 - Gretna, LA 70054-1519



### PRODUCT BULLETIN

## RP-645 - MIL-C-16173

Corrosion Preventive Compound, Solvent Cutback, Cold Application

#### **General Description**

**RP-645** is an dark colored, asphalt based, resilient coating designed to provide long term protection of metal surfaces. **RP-645** is applied as a solution in a volatile solvent. The residual film, after solvent evaporation, is highly resistant to salt water and salt spray. **RP-645** is supplied pre-dispersed in mineral spirits to simplify handling and application of the product. **RP-645** is formulated to meet the standards found in MIL-C-16173, Grade I and in testing was found to meet or exceed the performance parameters of that specification.

#### Performance Results

| Neat <b>RP-645</b> | Film Thickness |         | Days to Fail            | Days to Fail  | Days to Fail | Hours |
|--------------------|----------------|---------|-------------------------|---------------|--------------|-------|
|                    | Mils           | Microns | <b>Humidity Cabinet</b> | 5% Salt Spray | Salt Water   | Fail  |
|                    |                |         | on Polished Steel       |               | Immersion    | QUV   |
|                    | 3.50           | 88.90   | 60+                     | 45            | 14           | 1200+ |

#### **Application**

**RP-645** can be applied by dipping the parts to be protected in a vat or spraying the parts to be protected with air sprayers, pump type sprayers or by pouring the product over the parts. Removal of protective films is accomplished by using a steam cleaner or washing the parts in mineral spirits.

#### **Physical Properties**

Appearance Thick, Dark Brown to Black Liquid

Odor Solvent Odor

Specific Gravity 0.90 Flash Point (minimum) 108<sup>B</sup> F

Melting Point Liquid as Provided

**RP-645** meets or exceeds the following MIL-SPEC: MIL-C-16173, Grade 1.

#### **Availability**

RP-645 is available in UN approved 5 gallon pail, 55 gallon drums and bulk quantities.

#### Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.