

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094

PO Box 1519 - Gretna, LA 70054-1519



PRODUCT BULLETIN

TEKFLOC CP-753

Cationic Liquid Coagulant / Water Clarifier

General Description

TEKFLOC CP 626 is a low molecular weight, highly cationic liquid polyamine coagulant which effectively replaces, or significantly reduces, the need for primary inorganic metal salts in water or waste treatment. It is effective over a pH range of 1-12.

Application

TEKFLOC CP 753 is used as a primary coagulant in water treating, industrial & municipal waste treatment, mineral processing and oilfield applications. It can be effectively utilized in a broad range of liquid-solid separation processes such as settling, thickening, filtration, and dissolved air flotation. It is effective in clarification of low turbidity, highly colored waters. It can be used alone or in conjunction with an organic polymer flocculent. **TEKFLOC CP 753** is NSF approved for use in potable water at dosages up to 20 ppm. **TEKFLOC CP 753** is effective in treating turbid swimming pool water. Typical treatments for swimming pools are between 1 - 2 ppm of active polymer.

Physical Properties

Form @ 70° F	Straw Colored, Viscous Liquid
Odor	Mild
Specific Gravity	1.13 - 1.18
pH of 1% Solution	5.5 - 6.5
Freeze Point	20° F
Solubility in Water	Infinite
Viscosity @ 77° F	250 - 400 cps
Shelf Life @ 25° C	1 Year

Preparation and Feeding

TEKFLOC CP 753 can be diluted in-line with water to a concentration of 1% or less and added directly to the system. The product must be added at a point of high turbulence to assure the adequate mixing of coagulant with solids, followed by the maximum contact time possible. Alternately, a 1% stock solution can be prepared by simply adding the required volume of product to a tank containing water and mixing well. If required, the stock solution can then be further diluted in-line. The use of corrosion resistant pumps and tanks is recommended. Depending on the application, dosage levels for filtration and settling are between 1.02 and 3 ppm active polymer. Clarification is 1.0 to 20 ppm and dewatering sludge is 100 to 1000 ppm.

Availability

TEKFLOC-CP 753 is shipped in UN approved 275 gallon bulk tanks or in 55 gallon non-returnable, plastic drums.

Handling

TEKFLOC CP-753 should be stored in a heated building at a temperature of 40-95°F (5-35°C). When stored under these conditions, the product has a shelf life of at least one year. If frozen, the product should be allowed to thaw completely and mixed well prior to use. Neat polymer and polymer solutions should be stored in stainless steel, fiberglass, plastic or epoxy-lined tanks. Mild steel, iron, copper or aluminum should be avoided for both storage and feed equipment. Observe warning label on containers. Normal precautions for industrial chemicals apply.

The information contained herein is provided in good faith, but shall not create any warranty, expressed or implied, by operation of law or otherwise, with any respect to any product. JMN SPECIALTIES, INC. SPECIFICALLY DISCLAIMS ALL WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Phone (504) 341-3749 Fax (504) 341-5868 Internet e-mail: info@jmnspecialties.com