

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094
PO Box 1519 - Gretna, LA 70054-1519



PRODUCT BULLETIN

ABS SEALER

Asbestos, Glass and Rock Fiber Binding Solution and Sealer

General Description

ABS SEALER is a non-toxic, high acrylic solids, multi-purpose, ready-to-use, penetrating and bridging, encapsulant for all forms of friable asbestos. Apply with a low pressure airless sprayer for best results. **ABS SEALER** can be used for the encapsulation of ACM (Asbestos Containing Material) in place, so that they can remain in use without contributing to air-borne asbestos. **ABS SEALER** securely adheres to and *binds* friable ACM. When encapsulating ACM to remain in service, **ABS SEALER** can be applied in tow steps; by applying a penetrating coat to lock the fibers deep within the ACM and then by top coating as a thin film to the exposed (air stream) surfaces. **ABS SEALER** forms a clear, non-abrasive, flexible film for safe and effective handling of ACM. **ABS SEALER** has a temperature stability of 600° F. Coverage is dependent upon density and type of ACM being coated. **ABS SEALER** is effective on sealing fiber glass, rock fibers, and other types of mineral sealers and insulation to inhibit airborne fiber release.

Application

Do not dilute when used as a sealer. May be diluted with 2 parts water when used as a penetrant. Final top coat must be sprayed as provided. **ABS SEALER** must be applied with a low pressure airless sprayer. Coverage is dependent on penetration depth and absorption capacity of the surface being sealed. Clean up personnel and equipment with soap and water.

Physical Properties

Color (dry)	Clear (or custom tinted colors)
Odor	Slight Ammonia
Coverage	75 - 400 sq. ft./gal
Specific Gravity	1.030
Density	8.56 lbs./gallon
pH	< 10
Flash Point	None
Solubility	Soluble in Water
VOC (Volatile Organic Compounds)	None

Availability

ABS SEALER is available in 5 gallon pails, 55 gallon drums and bulk quantities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.

The information contained herein is provided in good faith, but shall not create any warranty, expressed or implied, by operation of law or otherwise, with any respect to any product. JMN SPECIALTIES, INC. SPECIFICALLY DISCLAIMS ALL WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Phone (504) 341-3749 Fax (504) 341-5868 or E-mail: info@jmnspecialties.com