

1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:	. CABINET STRIPPER 300
CHEMICAL NAME/	
CLASS/SYNONYMS:	None
PRODUCT NUMBER:	. CABINET STRIPPER 300
UN/NA NUMBER:	. 1759
CHEMICAL FAMILY:	. Compounds, Cleaning
CAS NUMBER:	. Mixture
FORMULA:	. Proprietary
COMPANY:	. JMN Specialties, Inc.
COMPANY:	. JMN Specialties, Inc. 1100 Victory Drive – Westwego, Louisiana USA 70094
COMPANY:	•
COMPANY:	1100 Victory Drive – Westwego, Louisiana USA 70094
	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868
	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868 www.jmnspecialties.com
	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868 <u>www.jmnspecialties.com</u> . CALL CHEMTEL: Toll Free US & Canada: (800) 255-3924, Outside USA +01-813-248-0585.

2 – HAZARDS IDENTIFICATION

GHS HAZARD CLASSIFICATION:

Physical Hazards

Health Hazards

WARNING LABEL ITEMS INCLUDING PRECAUTIONARY STATEMENTS:



SIGNAL WORD:..... DANGER!

GHS HAZARD AND PRECAUTIONARY STATEMENTS:

H300 H310 H330: Fatal if swallowed, in contact with skin or if inhaled

- H341: Suspected of causing genetic defects
- H361: Suspected of damaging fertility or the unborn child

P101+102+103: If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Read label before use.

P202+270+280+281: Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations, and product characteristics at time of disposal.

TOTAL VOC's:

None

3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER
Sodium Hydroxide	60 - 90	1310-73-2
Polyhydroxyacid Salt	15 - 30	527-07-1
Sodium alkylnaphthalenesulfonate	1 - 5	Confidential
Flash rust inhibitor	1 - 5	Confidential

4 – FIRST-AID MEASURES

BREATHING (INHALATION):	Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial resuscitation. Keep person warm and at rest. Treat symptomatically and supportively. Seek medical attention immediately. Qualified medical personnel should consider
SWALLOWING (INGESTION):	administering oxygen. Give large amounts of fresh water or milk immediately. Do not give anything by mouth if person is unconscious or otherwise unable to swallow. If vomiting occurs, keep head below hips to prevent aspiration. Treat symptomatically and supportively. Seek medical attention immediately.
EYES:	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
SKIN (DERMAL):	Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.
NOTE TO PHYSICIAN:	May cause caustic burns to the mouth, throat or stomach if swallowed. After swallowing danger of stomach perforation. On inhalation: Irritation of mucous membrane, coughing and shortness of breath. All treatments should be based on observed signs and symptoms of distress in the patient. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

5 – FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS:	• Fire fighters should wear full protective clothing, including self- contained breathing equipment.
AUTOIGNITION TEMP: EXTINGUISHING MEDIA:	• NA Determined by surrounding material. In case of fire, use water fog, dry
	chemical, CO_2 , or "alcohol" foam.



Safety Data Sheet (CABINET STRIPPER 300)

SPECIAL FIRE FIGHTING	. No action shall be taken involving any personal risk or without suitable
I ROCEDUKES.	
	training. Evacuate surrounding areas. Keep unnecessary and
	unprotected personnel from entering. Do not touch or walk through
	spilled material. Provide adequate ventilation. Wear appropriate
	respirator when ventilation is inadequate. Put on appropriate personal
	protective equipment. Spilled product may be slippery.
UNUSUAL FIRE AND	
EXPLOSION HAZARDS:	. Containers may explode from internal pressure if confined to fire. Cool
	with water spray

6 – ACCIDENTAL RELEASE MEASURES

	Wear appropriate personal protective equipment before approaching spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in accordance with applicable regulations. Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with
RCRA STATUS:	applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. Sodium Hydroxide (Caustic Soda), if discarded or spilled, as well as other wastes generated during use of sodium hydroxide or containing sodium hydroxide may exhibit one or more hazardous waste characteristics under 40 CFR 261.24: D002 – Corrosive.
	7 – HANDLING and STORAGE

STORAGE:	Keep in a tightly closed container, stored in a cool, dry, ventilated area below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe
	all warnings and precautions listed for the product. Drum must not be washed out or used for other purposes.
HANDLING:	• Avoid contact with eyes, skin and clothing. Do not inhale vapors and
	fumes. Wash thoroughly after handling. Use only with adequate ventilation. Do not take internally. For industrial use only.




8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

Sodium Hydroxide

Polyhydroxyacid Salt Sodium alkylnaphthalenesulfonate Flash rust inhibitor PEL 2 mg/m³ **TLV-TWA** 2 mg/m^3

None Established None Established





EXPOSURE CONTROLS:	Good general ventilation (typically 10 air changes per hour) should be
	used. Ventilation rates should be matched to conditions. If applicable,
	use process enclosures, local exhaust ventilation, or other engineering
	controls to maintain airborne levels below recommended exposure
	limits. If exposure limits have not been established, maintain airborne
	levels to an acceptable level. Please refer to the ACGIH document,
	Industrial Ventilation, A Manual of Recommended Practices, most
	recent edition, for details.
RESPIRATORY PROTECTION	I : If engineering controls do not maintain airborne concentrations below
	recommended exposure limits (where applicable) or to an acceptable
	level (in countries where exposure limits have not been established), an
	approved respirator must be worn. In the United States of America, if
	respirators are used, a program should be instituted to assure
	compliance with OSHA Standard 63 FR 1152, January 8, 1998.
	Respirator type: Air-purifying respirator with an appropriate,
	government approved (where applicable), air-purifying filter, cartridge
	or canister. Contact health and safety professional or manufacturer for
	specific information.
PROTECTIVE CLOTHING:	Eye/face protection: Wear chemical goggles; face shield (if splashing
	is possible). Skin protection: Chemical resistant, impermeable gloves.
	Gloves should be tested to determine suitability for prolonged contact.
	Use of impervious apron or chemical suit and chemical resistant boots
	are recommended.
ADDITIONAL MEASURES:	Handle in accordance with good industrial hygiene and safety practice.
ADDITIONAL MEASURES.	Wash thoroughly with soap and water after handling and before eating,
	drinking, or using tobacco. Safety shower and eye wash should be
	available close to work areas.
	available close to work aleas.

9 – PHYSICAL / CHEMICAL PROPERITES

BOILING POINT:2534°F (1390°C)FREEZING POINT:NAFLASHPOINT:Non-flammable materialUPPER FLAME LIMIT (%):NA



NA
ND
ND
1.18 - 2.10
1% solution 14.0
Complete
None
No data available (G/MOLE)
NA
Granular solids
Off White
Bland

10 – STABILITY and REACTIVITY

STABILITY: HAZARDOUS DECOMP.: INCOMPATIBILITY:	
HAZARDOUS REACTIONS:	Dissolution of CS 300 in water is highly exothermic (will generate heat), and the resulting heat may cause heat burns or ignite flammables. It also produces heat when reacted with acids.

11 – TOXICOLOGICAL INFORMATION

THRESHOLD LIMIT VALUE: OSHA PEL: LISTED CARCINOGEN:	2 mg/m ³ 2 mg/m ³ This product IS NOT listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest editions) or found to be a potential carcinogen by OSHA.
MEDICAL CONDITION AGGRAVATED:	• Pre-existing medical conditions of the following organ(s) or organ
	system(s) may be aggravated by exposure to this material: Respiratory system. Eyes. Skin.



INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS

ORAL

DERMAL

INHALATION

Product: Effects due to inhalation of dusts or mist may vary from mild irritation of the nose at 2 mg/m^3 to severe pneumonitis depending on the severity of exposure. Low concentrations may cause mucous membrane irritation with sore throat, coughing, and dyspnea. Intense exposures may result in destruction of mucous membranes and delayed pulmonary edema or pneumonitis. Shock may occur.

REPEATED DOSE TOXICITY

SKIN CORROSION / IRRITATION

SERIOUS EYE DAMAGE / IRRITATION

RESPIRATORY OR SKIN SENSITIZATION



MUTAGENCITY

IN VITRO	
Product:	No Data Available
IN VIVO	
Product:	No Data Available
Specified Substance(s)	Information as provided by manufacturer
Sodium Hydroxide, bead	No Data Available

CARCINOGENICITY

REPODUCTIVE TOXICITY

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE

Product: GENERAL: This product contains highly alkaline ingredients. **INHALATION:** Exposure to vapor, mist or liquid can cause mild to severe irritation to the respiratory tract, including chemical burns. Severe exposures could result in chemical pneumonia. **EYES:** Contact can cause severe damage including burns and blindness. The severity of the effects depend on concentration and how soon after exposure the eyes are washed. **SKIN:** Brief contact may cause slight to mild irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain, local redness and swelling and possible tissue damage. **INGESTION:** Severe irritant. May cause severe burns of the mucous membranes of the mouth, esophagus, and stomach.

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE

Product: CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. **TERATOGENIC EFFECTS:** Not available. **DEVELOPMENTAL TOXICITY:** Not available. The substance is toxic to lungs. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

ASPIRATION HAZARD

OTHER ADVERSE EFFECTS

12 – ECOLOGICAL INFORMATION

ACUTE TOXICITY

FISH

Product:.....Bluegill sunfish: 48-hour LC50 = 99 mg/L Mosquito fish: 96-hour LC50 = 125 mg/L Brown shrimp (Crangon crangon): 48-hour LC50 = 30 - 100 mg/L AQUATIC INVERTEBRATES



CHRONIC TOXICITY

FISH

AQUATIC INVERTEBRATES

Product:......Expected to have low toxicity: 10 < LC/EC/IC50 <= 100 mg/l **TOXICITY TO AQUATIC PLANTS**

Product: Freshwater algae are destroyed above pH 8.5.

PERSISTENCE AND DEGRADABILITY

BIODEGRADATION

BIOLOGICAL OXYGEN DEMAND

Product: No data available

CHEMICAL OXYGEN DEMAND

Product: No data available

BOD / COD RATIO

Product: No data available

BIOACCUMULATIVE POTENTIAL

MOBILITY IN SOIL

Product: Expected to partition to water. The pH effect of sodium hydroxide in water is naturally reduced by the absorption of atmospheric carbon dioxide. This reduction is also effected by dilution with water and by the natural acidity of a given water body. There is no degradation of sodium hydroxide in waters, only loss by absorption or through chemical neutralization.

RESULTS OF PBT AND mPvB ASSESSMENT

Product:......Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria. Not fulfilling vPvB (very persistent, very bioaccumulative) criteria.

OTHER ADVERSE EFFECTS

Product: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.



other wastes generated during use of sodium hydroxide or containing sodium hydroxide may exhibit one or more hazardous waste characteristics under 40 CFR 261.24: D002 - Corrosive.

14 – TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.



UN/NA NUMBER:	1759
PROPER SHIPPING NAME:	Corrosive solids, n.o.s. Contains (Sodium Hydroxide)
HAZARD CLASS:	8
PACKAGING GROUP :	II
LETTER:	C (Corrosive substances)
ENVIRONMENTAL HAZARD:	Caustic soda does not bioaccumulate due to its high solubility in water.
	It is considered slightly toxic to aquatic organisms unless there is a
	significant pH shift outside the range of $5 - 10$, which may be toxic to
	aquatic organisms.
REPORTABLE QUANTITY:	800# based on Sodium Hydroxide in mixture.

15 - REGULATIONS

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). IMPORTANT: Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

EPA SRA Title III Chemical Listings:

TSCA STATUS:	• This product is listed on the TSCA inventory. If this product is a blend, all ingredients in the product are listed on the TSCA Inventory List. Any impurities present in this product are exempt from listing.
SECTION 302:	None
SECTION 304:	. None
SECTION 312:	Yes
SARA SECTION 313:	SECTION 313 REPORTABLE INGREDIENTS (40 CFR 372):
	This product contains toxic chemicals subject to the reporting requirements of Section 313, Title III of the SARA (Superfund Amendments and Reauthorization Act) of 1986: Sodium Hydroxide (Caustic Soda)
ACUTE:	. Yes
CHRONIC:	
FIRE:	
PRESSURE:	. No
REACTIVE:	. Yes
CLEAN WATER ACT:	None



IMDG – International Marine Dangerous Goods Code

UN1759, Corrosive Solid, N.O.S. Contains (Sodium Hydroxide), 8, PG II. EmS F-A, S-B. Marine Pollutant: No.

IATA

UN1759, Corrosive Solid, N.O.S. Contains (Sodium Hydroxide), 8, PG II.

DEA Chemical Trafficking Act: .. No

16 – OTHER INFORMATION

HMIS*		
HEALTH	3	
FLAMMABILITY	0	
REACTIVITY	0	
PERSONAL PROTECTIO	ON H	

***HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard.** HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.

ND = No Data, NA = Not Applicable/Not Available, \leq = Less than or equal to, \geq = Greater than or equal to

REVISION STATEMENT: Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH **INFORMATION REFERS.**

This is the last page of this SDS