



Safety Data Sheet (881 SOLVENT / THINNER)

1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:..... 881 SOLVENT / THINNER

CHEMICAL NAME/

CLASS/SYNONYMS:..... Paint Thinner

PRODUCT NUMBER: 881 SOLVENT / THINNER

UN/NA NUMBER: 1993

CHEMICAL FAMILY: Solvent

CAS NUMBER: Not applicable for mixtures.

FORMULA: Proprietary

COMPANY:..... **JMN Specialties, Inc.**

1100 Victory Drive – Westwego, Louisiana USA 70094

Phone (504) 341-3749, Fax (504) 341-5868

www.jmnspecialties.com

EMERGENCY PHONE: CALL CHEMTEL: Toll Free US & Canada: (800) 255-3924, Outside
USA +01-813-248-0585. Contract #: MIS0002833.

DATE PREPARED: February 29, 2016

2 – HAZARDS IDENTIFICATION

GHS HAZARD CLASSIFICATION:

Physical Hazards

Flammable Liquids:..... . Category 2 - Highly flammable liquid and vapor

Health Hazards

Acute Toxicity (Oral): Category 4 - Harmful if swallowed, in contact with skin, inhaled

Skin Corrosion/Irritation: Category 2 - Causes skin irritation

Serious Eye Damage/Irritation: Category 2A - Causes eye irritation

Aspiration Hazard:..... . Category 1 - May be fatal if swallowed and enters airways

WARNING LABEL ITEMS INCLUDING PRECAUTIONARY STATEMENTS:

Pictograms:



SIGNAL WORD:..... DANGER!

GHS HAZARD AND PRECAUTIONARY STATEMENTS:

H303 H313 H333: May be harmful if swallowed, in contact with skin or if inhaled

H305: May be harmful if swallowed and enters airways

P101+102+103: If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Read label before use.

P202+270+280+281: Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



Safety Data Sheet (881 SOLVENT / THINNER)

P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

TOTAL VOC's: 4.20 pounds per gallon

3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER
Toluene	50 - 70	108-88-3
Acetone	30 - 40	67-64-1
Isopropyl alcohol	5 - 15	67-63-0

4 – FIRST-AID MEASURES

BREATHING (INHALATION): Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial resuscitation. Keep person warm and at rest. Treat symptomatically and supportively. Seek medical attention immediately. Qualified medical personnel should consider administering oxygen.

SWALLOWING (INGESTION): Give large amounts of fresh water or milk immediately. Do not give anything by mouth if person is unconscious or otherwise unable to swallow. If vomiting occurs, keep head below hips to prevent aspiration. Treat symptomatically and supportively. Seek medical attention immediately.

EYES: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

SKIN (DERMAL):..... Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.

NOTE TO PHYSICIAN: All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Material, if aspirated into the lungs, may cause chemical pneumonitis. Skin contact may aggravate an existing dermatitis. Treat appropriately.

5 – FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS: Flammable liquid and vapor

AUTOIGNITION TEMP:..... 750°F (399°C) Estimated

EXTINGUISHING MEDIA: Determined by surrounding material. In case of fire, use water fog, dry chemical, CO₂, or "alcohol" foam.



Safety Data Sheet (881 SOLVENT / THINNER)

SPECIAL FIRE FIGHTING

PROCEDURES: Spilled product on ground may be slippery. Spilled product will float on water. Spilled product is flammable.

UNUSUAL FIRE AND

EXPLOSION HAZARDS: Containers may explode from internal pressure if confined to fire. Cool with water spray. Vapor accumulation could flash or explode if in contact with an open flame.

6 – ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES: Wear appropriate personal protective equipment before approaching spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in accordance with applicable regulations.

WASTE DISPOSAL: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

7 – HANDLING and STORAGE

STORAGE: Keep in a tightly closed container, stored in a cool, dry, ventilated area below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Drum must not be washed out or used for other purposes.

HANDLING: Avoid contact with eyes, skin and clothing. Do not inhale vapors and fumes. Wash thoroughly after handling. Use only with adequate ventilation. Do not take internally. For industrial use only.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS INGREDIENT	PEL	TLV-TWA
Toluene	150 ppm	100 ppm TWA
Acetone	750 ppm	750 ppm TWA
Isopropyl alcohol	400 ppm	400 ppm TWA





Safety Data Sheet (881 SOLVENT / THINNER)

- EXPOSURE CONTROLS:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.
- RESPIRATORY PROTECTION:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Self-Contained Breathing Apparatus may be required for use in confined or enclosed spaces.
- PROTECTIVE CLOTHING:** **Eye/face protection:** Wear chemical goggles; face shield (if splashing is possible). **Skin protection:** Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron or chemical suit and chemical resistant boots are recommended.
- ADDITIONAL MEASURES:** Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

9 – PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT:..... 138 - 229°F (58 - 110°C)
FREEZING POINT: < 0°F
FLASHPOINT:..... 0°F (-18°C)
UPPER FLAME LIMIT (%): 7.1%
LOWER FLAME LIMIT (%): ... 1.2%
VAPOR PRESSURE:..... For lowest component: 24 kPa @ 68°F (20°C)
VAPOR DENSITY (AIR=1):..... 2.6
SPECIFIC GRAVITY: 0.83 - 0.85
pH: NA
SOLUBILITY IN WATER:..... Approximately 10% Soluble

VOLATILITY
INCLUDING WATER: 7.00 pounds per gallon
MOLECULAR WEIGHT: No data available (G/MOLE)
EVAPORATION RATE:..... > 1
PHYSICAL STATE: Liquid
COLOR: Clear
ODOR:..... Aromatic solvent



Safety Data Sheet (881 SOLVENT / THINNER)

10 – STABILITY and REACTIVITY

STABILITY: Stable
HAZARDOUS DECOMP.: Will not occur
INCOMPATIBILITY: Oxidizers or Oxidizing Materials.
HAZARDOUS REACTIONS: Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).

11 – TOXICOLOGICAL INFORMATION

Cancer: Research shows that toluene is unlikely to cause cancer. **Reproductive Effects:** There are no indications toluene causes damage to reproductive organs. Toluene may affect the development of unborn babies. **Organ Systems:** Damage to the brain, liver, bone marrow and kidneys can occur.

THRESHOLD LIMIT VALUE:.. 100 ppm based on Toluene in blend.
OSHA PEL: 100 ppm
LISTED CARCINOGEN: Toluene: No carcinogenic effects were observed when toluene was applied to the skin of mice for two years. A 2 year NTP inhalation study (rodents) at levels up to 1200 ppm toluene was negative. Prolonged or repeated exposure to toluene does not result in bone marrow injury or blood changes characteristic of benzene.

MEDICAL CONDITION

AGGRAVATED: Existing dermatitis.

INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS

ORAL

Product: Toluene: (Rats): LD50: > 7 000 mg/kg. Considered to be practically non-toxic based on single dose level testing at 7000 mg/kg. Warning Hazard category 5. Practically non-toxic, but when swallowed can cause lung damage.

DERMAL

Product: Toluene: (Rats): LD50: > 7 000 mg/kg. Considered to be practically non-toxic based on single dose level testing at 7000 mg/kg. Warning Hazard category 5. Practically non-toxic, but when swallowed can cause lung damage.

INHALATION

Product: Toluene: (Rats): Harmful (LC50: greater than 10 but less than 20mg/l) 4 hours. Based on testing of similar products and/or the components. Warning Hazard category 4. Harmful if inhaled.

REPEATED DOSE TOXICITY

Product: Toluene: (Rats): Application Route: Inhalation Dose: 0, 100, 625, 1250, 3000 ppm. Exposure time: 15 weeks. Number of exposures: 6.5 h/d, 5 day/week: NOEL: 625 ppm.

SKIN CORROSION / IRRITATION

Product: Repeated and prolonged exposure to concentrated material may cause dermatitis.

SERIOUS EYE DAMAGE / IRRITATION

Product: Toluene: (Rabbits): Practically non-irritating. Eye irritation scores: 12.0 at 24 hours, 18.0 at 48 hours, 18.0 at 72 hours, 16.0 at 4 days, 9.0 at 7 days. Warning Hazard category 2B. May cause mild eye irritation.

RESPIRATORY OR SKIN SENSITIZATION

Product: Not expected to be sensitizing based on tests of this product, components, or similar products.



Safety Data Sheet (881 SOLVENT / THINNER)

MUTAGENICITY

IN VITRO

Product:..... No Data Available

IN VIVO

Product:..... No Data Available

Specified Substance(s)

Information as provided by manufacturer

Toluene

No Data Available

CARCINOGENICITY

Product:..... **Cancer, Reproductive and other Chronic Hazards:** Leukemia has been reported in humans from Benzene. This product contains less than 186 ppm of Benzene. This is not considered hazardous in such low concentrations. **Toxicological Data for Toluene:** Oral rat LD₅₀: 636 mg/kg; skin rabbit LD₅₀: 14100 uL/kg; inhalation rat LC₅₀: 49 gm/m³/4H; Irritation data: skin rabbit, 500 mg, Moderate; eye rabbit, 2 mg/24H, Severe. Investigated as a tumorigen, mutagen, reproductive effector. Reproductive Toxicity: Has shown some evidence of reproductive effects in laboratory animals.

REPRODUCTIVE TOXICITY

Product:..... The NOEL for toluene was 500 ppm. Levels greater than 1500 ppm may adversely affect fetal development. Warning Hazard category 2.

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE

Product: **GENERAL:** Solvent vapors may be irritating to skin and eyes. **INHALATION:** High concentrations of vapor may cause irritation of the respiratory tract, experienced as nasal discomfort and discharge, possibly with chest pain and coughing. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. **EYES:** May cause mild to severe irritation experienced as discomfort or pain, excess blinking and tear production, possibly with marked redness and swelling of the conjunctiva. **SKIN:** Brief contact may cause slight irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain. **SWALLOWING:** May cause headache, dizziness, nausea, vomiting, diarrhea, coma, and death.

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE

Product:..... The effects of long-term, low-level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the avoidance of all effects from repetitive acute exposure. This product may aggravate existing eye, skin, and respiratory conditions.

ASPIRATION HAZARD

Product:..... Droplets of the product aspirated into the lungs through ingestion or vomiting may cause chemical pneumonia.

OTHER ADVERSE EFFECTS

Product:..... In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

12 – ECOLOGICAL INFORMATION

ACUTE TOXICITY

FISH

Product:..... (Salmon) LC/EC50: 8.1 mg/l at 96 hours.

AQUATIC INVERTEBRATES

Product:..... (Daphnia magna) LC/EC50: 6 mg/l at 48 hours.



Safety Data Sheet

(881 SOLVENT / THINNER)

CHRONIC TOXICITY

FISH

Product: This material has exhibited moderate toxicity to aquatic organisms.

AQUATIC INVERTEBRATES

Product: This material has exhibited moderate toxicity to aquatic organisms.

TOXICITY TO AQUATIC PLANTS

Product: (Green algae) LC/EC50: 9.4 mg/l at 8 hours.

PERSISTENCE AND DEGRADABILITY

BIODEGRADATION

Product: Based on components, product is classified as Readily Biodegradable.

BIOLOGICAL OXYGEN DEMAND

Product: No data available

CHEMICAL OXYGEN DEMAND

Product: No data available

BOD / COD RATIO

Product: No data available

BIOACCUMULATIVE POTENTIAL

Product: Bioconcentration factor (BCF) < 100.

MOBILITY IN SOIL

Product: Water solubility: approximately 10 - 15% by volume

RESULTS OF PBT AND mPvB ASSESSMENT

Product: Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria. Not fulfilling vPvB (very persistent, very bioaccumulative) criteria.

OTHER ADVERSE EFFECTS

Product: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13 –DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.



Safety Data Sheet (881 SOLVENT / THINNER)

14 – TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.



UN/NA NUMBER: 1993
PROPER SHIPPING NAME: Flammable Liquid, n.o.s., Contains (Toluene, Acetone, Isopropyl Alcohol)
HAZARD CLASS:..... 3
PACKAGING GROUP :..... II
LETTER:..... F (Highly flammable)
ENVIRONMENTAL HAZARD: Potential Marine Pollutant
REPORTABLE QUANTITY: 1667# (756.14 kilograms) based on Toluene (CAS# 108-88-3) in blend.

15 - REGULATIONS

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). **IMPORTANT:** Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

EPA SRA Title III Chemical Listings:

TSCA STATUS:..... This product is listed on the TSCA inventory. If this product is a blend, all ingredients in the product are listed on the TSCA Inventory List.
Any impurities present in this product are exempt from listing.
SECTION 302:..... None
SECTION 304:..... None
SECTION 312:..... Yes
SARA SECTION 313:..... 1667# (756.14 kilograms) based on Toluene (CAS# 108-88-3) in blend.
ACUTE:..... Yes
CHRONIC: Yes
FIRE: Yes
PRESSURE:..... No
REACTIVE:..... No
CLEAN WATER ACT: None

IMDG – International Marine Dangerous Goods Code

UN1993, Flammable Liquid, N.O.S Contains (Toluene, Acetone, Isopropyl Alcohol) 3, F, PGII. EmS F-E, S-E. Marine Pollutant: Yes. Static Accumulator: Yes.

IATA

UN1993, Flammable Liquid, N.O.S Contains (Toluene, Acetone, Isopropyl Alcohol) 3, F, PGII.

DEA Chemical Trafficking Act:.. U.S. Drug Enforcement Administration Chemical Diversion and Trafficking Act: Sales, receipts, movements or unexplained losses of this chemical may require recordkeeping and reporting in accordance with 21 CFR 1310/1313.



Safety Data Sheet (881 SOLVENT / THINNER)

16 – OTHER INFORMATION

HMIS*

HEALTH		3
FLAMMABILITY		2
REACTIVITY		0
PERSONAL PROTECTION		H

**HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard. HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.*

ND = No Data, NA = Not Applicable/Not Available, ≤ = Less than or equal to, ≥ = Greater than or equal to

REVISION STATEMENT: Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. **NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.**

*****This is the last page of this SDS*****