

#### 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:...... USES VC CLEANER

CHEMICAL NAME/

CLASS/SYNONYMS: ...... Solvent Degreasing Agent PRODUCT NUMBER: ...... USES VC CLEANER

**UN/NA NUMBER: .....** 1268

CHEMICAL FAMILY: ...... Compounds, Cleaning Liquid

CAS NUMBER: ..... Mixture

composition will vary.

COMPANY:.....JMN Specialties, Inc.

1100 Victory Drive - Westwego, Louisiana USA 70094

Phone (504) 341-3749, Fax (504) 341-5868

www.jmnspecialties.com

EMERGENCY PHONE: ...... CALL CHEMTEL: Toll Free US & Canada: (800) 255-3924, Outside

USA +01-813-248-0585.

DATE PREPARED: ..... February 28, 2019

#### 2 - HAZARDS IDENTIFICATION

#### GHS HAZARD CLASSIFICATION:

Physical Hazards

**Health Hazards** 

**Skin Corrosion/Irritation:** ...... Catagory 2 - Causes skin irritation **Serious Eye Damage/Irritation:** Catagory 2A - Causes eye irritation

**Aspiration Hazard:......** Catagory 1 - May be fatal if swallowed and enters airways

#### WARNING LABEL ITEMS INCLUDING PRECAUTIONARY STATEMENTS:

**Pictograms:** 







SIGNAL WORD:...... DANGER!

#### GHS HAZARD AND PRECAUTIONARY STATEMENTS:

H303 H313 H333: May be harmful if swallowed, in contact with skin or if inhaled H305: May be harmful if swallowed and enters airways

P101+102+103: If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Read label before use.

P202+270+280+281: Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

TOTAL VOC's: ...... 7.17 pounds per gallon

### 3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER
Petroleum Solvent Naphtha, Heavy Aromatic	50 - 60	64742-95-6
Aliphatic Hydrocarbon	40 - 50	64742-47-8

#### 4 - FIRST-AID MEASURES

4 – FIRST-AID MEASURES		
<b>BREATHING (INHALATION)</b> :	Remove from exposure area to fresh air immediately. If breathing has	
	stopped, perform artificial resuscitation. Keep person warm and at rest.	
	Treat symptomatically and supportively. Seek medical attention	
	immediately. Qualified medical personnel should consider	
	administering oxygen.	
SWALLOWING (INGESTION):	Give large amounts of fresh water or milk immediately. Do not give	
	anything by mouth if person is unconscious or otherwise unable to	
	swallow. If vomiting occurs, keep head below hips to prevent	
	aspiration. Treat symptomatically and supportively. Seek medical	
	attention immediately.	
EYES:		
	occurs, obtain medical attention.	
SKIN (DERMAL):		
~ (	water. If persistent irritation occurs, obtain medical attention. When	
	using high pressure equipment, injection of product under the skin can	
	occur. If high pressure injuries occur, the casualty should be sent	
	immediately to a hospital. Do not wait for symptoms to develop.	
NOTE TO PHYSICIAN:	• • • • • • • • • • • • • • • • • • • •	
NOTE TO THIS CLAIM.		
	distress in the patient. Consideration should be given to the possibility	
	that overexposure to materials other than this product may have	
	occurred. Material, if aspirated into the lungs, may cause chemical	
	pneumonitis. Skin contact may aggravate an existing dermatitis. Treat	
	appropriately.	



#### 5 - FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS: .... Flammable liquid and vapor

**AUTOIGNITION TEMP:....** 842°F (450°C)

**EXTINGUISHING MEDIA:** Determined by surrounding material. In case of fire, use water fog, dry

chemical, CO<sub>2</sub>, or "alcohol" foam. Firefighting should be attempted only by those who are adequately trained and equipped with proper

protective equipment.

SPECIAL FIRE FIGHTING

**PROCEDURES:** 

Spilled product on ground may be slippery.

UNUSUAL FIRE AND

**EXPLOSION HAZARDS:.....** Containers may explode from internal pressure if confined to fire. Cool

with water spray. Vapor accumulation could flash or explode if in

contact with an open flame.

#### 6 - ACCIDENTAL RELEASE MEASURES

**SPILL PROCEDURES:** ...... Wear appropriate personal protective equipment before approaching

spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in

accordance with applicable regulations.

WASTE DISPOSAL: ...... Treatment, storage, transportation and disposal must be in accordance

with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in

accordance with federal, state and local requirements.

RCRA STATUS:...... If discarded in its purchased form, this product is considered a RCRA

hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should

be classified as a hazardous waste. (40CFR261.20-24).

#### 7 – HANDLING and STORAGE

**STORAGE:** Keep in a tightly closed container, stored in a cool, dry, ventilated area

below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Drum must not be

washed out or used for other purposes.

**HANDLING:** Avoid contact with eyes, skin and clothing. Do not inhale vapors and

fumes. Wash thoroughly after handling. Use only with adequate

ventilation. Do not take internally. For industrial use only.



#### 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS INGREDIENT PEL **TLV-TWA** Petroleum Solvent Naphtha, Heavy Aromatic 10 ppm 10 ppm Aliphatic Hydrocarbon 100 ppm 100 ppm







#### **EXPOSURE CONTROLS:**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

**RESPIRATORY PROTECTION:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Self-Contained Breathing Apparatus may be

#### PROTECTIVE CLOTHING:

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible). Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron or chemical suit and chemical resistant boots are recommended.

#### ADDITIONAL MEASURES:

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

#### 9 - PHYSICAL / CHEMICAL PROPERITES

required for use in confined or enclosed spaces.

**BOILING POINT:.....** 352°F (178°C) **FREEZING POINT:** ..... - 4°F (-20°C) **FLASHPOINT:....** 150°F (65.5°C)

**UPPER FLAME LIMIT (%): .....** 7.0% LOWER FLAME LIMIT (%): ... 0.6% VAPOR PRESSURE:..... ND



**VAPOR DENSITY (AIR=1):.....** > 1

**SPECIFIC GRAVITY: .....** 0.93 - 0.95

**pH:** ...... NA

**SOLUBILITY IN WATER:.....** Negligible

VOLATILITY

INCLUDING WATER: ...... 7.80 pounds per gallon

MOLECULAR WEIGHT: ...... No data available

EVAPORATION RATE:................ 0.05
PHYSICAL STATE:......Liquid
COLOR:......Clear

ODOR:..... Aromatic solvent

#### 10 - STABILITY and REACTIVITY

STABILITY: ...... Stable

HAZARDOUS DECOMP.:..... Will not occur

**INCOMPATIBILITY:** ...... Oxidizers or Oxidizing Materials.

**HAZARDOUS REACTIONS:** Not expected to be Explosive, Self-Reactive, Self-Heating, or an

Organic Peroxide under US GHS Definition(s).

#### 11 - TOXICOLOGICAL INFORMATION

**Cancer:** Research shows that the Solvents used in the mixture are unlikely to cause cancer. **Reproductive Effects:** There are no indications that the Solvents used in the mixture causes damage to reproductive organs. Solvents may affect the development of unborn babies. **Organ Systems:** Damage to the brain, liver, bone marrow and kidneys can occur with repeated or excessive inhalation of any solvent vapors.

THRESHOLD LIMIT VALUE:.. 10 ppm

**OSHA PEL:....** 10 ppm

of the property. No data to designate product to cause specific target

organ toxicity through repeated exposure.

MEDICAL CONDITION

**AGGRAVATED:** Existing dermatitis.

#### INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS

#### **ORAL**

#### INHALATION

**Product:** High vapor/aerosol concentrations (attainable at elevated temperatures well above ambient) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anaesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death effects, including death.

#### REPEATED DOSE TOXICITY



#### SKIN CORROSION / IRRITATION

**Product:** Repeated and prolonged exposure to concentrated material may cause dermatitis.

#### SERIOUS EYE DAMAGE / IRRITATION

**Product:** Practically non-irritating. Slightly irritating but does not injure eye tissue.

#### RESPIRATORY OR SKIN SENSITIZATION

#### MUTAGENCITY

#### IN VITRO

**Product:** No Data Available

#### IN VIVO

**Product:** ...... No Data Available

Specified Substance(s) Information as provided by manufacturer

Petroleum Distillates No data available

#### **CARCINOGENICITY**

**Product:** Based on available data, the classification criteria are not met.

#### REPODUCTIVE TOXICITY

#### SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

**Product: GENERAL:** Solvent vapors may be irritating to skin and eyes. **INHALATION:** High concentrations of vapor may cause irritation of the respiratory tract, experienced as nasal discomfort and discharge, possibly with chest pain and coughing. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. **EYES:** May cause mild to severe rritation experienced as discomfort or pain, excess blinking and tear production, possibly with marked redness and swelling of the conjunctiva. **SKIN:** Brief contact may cause slight irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain. **SWALLOWING:** May cause headache, dizziness, nausea, vomiting, diarrhea, coma, and death.

#### SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

#### ASPIRATION HAZARD

### OTHER ADVERSE EFFECTS

**Product:** LD<sub>50</sub> (oral) 7050, 8400mg/kg (rat), above 5000mg/kg (rat), LD50 (skin) >2000 & >3160mg/kg (rabbit) - no mortality recorded in these tests. LC<sub>50</sub> (inhalation) 5100 & 11,400mg/m 3 (rat), above 590mg/m 3 (rat). Chronic Toxicity NOAEL (oral) 300mg/kg/day (rats - various toxic symptoms - 90 days). LOAEL (skin) 119mg/kg (applied twice weekly - 50 weeks) (mouse, lung symptoms). NOAEC (inhalation) 2430mg/m 3 (rats - reproduction).



this product.

# Safety Data Sheet (USES VC CLEANER)

### 12 - ECOLOGICAL INFORMATION

ACUTE TOXICITY
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
CHRONIC TOXICITY
FISH
<b>Product:</b> This material has exhibited slight toxicity to terrestrial organisms.
AQUATIC INVERTEBRATES
<b>Product:</b>
TOXICITY TO AQUATIC PLANTS
<b>Product:</b> EC <sub>50</sub> (Algae) 2.5mg/liter (Skeletonema costatum), 4.2mg/liter
(Selenastrum capricornutum)
PERSISTENCE AND DEGRADABILITY
BIODEGRADATION
Product:
BIOLOGICAL OXYGEN DEMAND
Product:
CHEMICAL OXYGEN DEMAND
Product:
BOD / COD RATIO Product:
BIOACCUMULATIVE POTENTIAL
<b>Product:</b> Highly volatile, will partition rapidly to air. Not expected to partition
sediment and wastewater solids.
MOBILITY IN SOIL
Product:
RESULTS OF PBT AND mPvB ASSESSMENT
Product:
fulfilling vPvB (very persistent, very bioaccumulative) criteria.
OTHER ADVERSE EFFECTS
<b>Product:</b>
Trouble (e.g. september)

photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from



#### 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: ...... Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

RCRA STATUS:...... If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).

#### 14 - TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.



UN/NA NUMBER: ...... 1268

PROPER SHIPPING NAME: ..... Petroleum Distillates, n.o.s., Contains (Heavy Petroleum Naphtha)

HAZARD CLASS:..... 3 PACKAGING GROUP :..... III

**LETTER:**..... F (Highly flammable)

ENVIRONMENTAL HAZARD: Because of modern treatment methods or method of use of this product,

only an insignificant amount of the ingredients reaches the environment. That amount is at such levels as to typically not cause any adverse

effects.

REPORTABLE QUANTITY: ..... None

#### 15 - REGULATIONS

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). IMPORTANT: Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

#### **EPA SRA Title III Chemical Listings:**

TSCA STATUS: ...... This product is listed on the TSCA inventory. If this product is a blend, all ingredients in the product are listed on the TSCA Inventory List. Any impurities present in this product are exempt from listing. SECTION 302:..... None

**SECTION 304:.....** None **SECTION 312:....** Yes



 SARA SECTION 313:
 None

 ACUTE:
 Yes

 CHRONIC:
 Yes

 FIRE:
 Yes

 PRESSURE:
 No

 REACTIVE:
 No

 CLEAN WATER ACT:
 None

IMDG - International Marine Dangerous Goods Code

UN1268, Petroleum Distillates, N.O.S. Contains (Heavy Petroleum Naphtha), 3, PG III. EMS-No: F-E S-E. Marine pollutant: No.

**IATA** 

UN1268, Petroleum Distillates, N.O.S. Contains (Heavy Petroleum Naphtha), 3, PG III.

**DEA Chemical Trafficking Act:..** No

#### **16 – OTHER INFORMATION**

HMIS*		
HEALTH	1	
FLAMMABILITY	2	
REACTIVITY	0	
PERSONAL PROTECTI	ON C	

\*HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard. HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.

ND = No Data, NA = Not Applicable/Not Available,  $\leq = Less than or equal to$ ,  $\geq = Greater than or equal to$ 

**REVISION STATEMENT:** Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

#### DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. REPRESENTATIONS **EITHER EXPRESS** OR WARRANTIES, OR IMPLIED, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

\*\*\*This is the last page of this SDS\*\*\*